TECHNICAL INFORMATIONS
TAPE TERDUR 32

PRODUCT DESCRIPTION

Reinforced self-adhesive tape made of polyester film and non-woven fabric covered with acrylic adhesive. The tape has a high adaptability and adhesion, resistant to solvents.

APPLICATION

Recommended for fixing capacitors. Enables visual inspection of the correct contact assignment and general fixing of the connection windings.

CHARACTERISTICS

Colour	transparent
Backing thickness (mm)	0,07 + - 10%
Total thickness (mm)	0,12 ± 10%
Breakdown voltage min. (kV)	4.0
Tensile strength (min) (N/cm)	45
Elongation at break min. (%)	30
Adhesion on steel (N/cm)	5,5
Adhesive system	acrylic
Thermal class	F - 155°C

PACKAGE

The product is available in a roll with a length of 50 mb, standard widths: 12, 19 and 25 mm, dimensions from 10mm - 30mm.

EURODRUT
centrum drutów nawojowych

WWW.EURODRUT.PL
WWW.SKLEPEURODRUT.PL
INFO@EURODRUT.PL

EURODRUT SP. Z O.O. SP. K.
UL. GRUNWALDZKA 479
62-064 PLEWISKA POLAND

tel.: + 48 61 867 15 53
tel.: + 48 61 867 15 55