

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 1 of 12

Print date: 15/11/2016

### SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: DISOLVENTE M-2  
Product Code: DL101

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Varnishes and electro enamel thinner.

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **S.E.G. ROYAL-DIAMOND, S.A.**  
Address: Polígono Industrial s/n  
City: 08319 Dosrius  
Province: BARCELONA  
Telephone: 93-791-80-06  
Fax: 93-791-91-25  
E-mail: royaldiamond@royaldiamond.es  
Web: www.royaldiamond.es

**1.4 Emergency telephone number:** 00-34-93-791-80-06 (Only available during office hours; Monday-Friday; 08:00-18:00)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.  
Carc. 2 : Suspected of causing cancer.  
Eye Irrit. 2 : Causes serious eye irritation.  
Flam. Liq. 2 : Highly flammable liquid and vapour.  
Repr. 1B : May damage the unborn child.  
STOT SE 3 : May cause drowsiness or dizziness.

#### 2.2 Label elements.

**Labelling in accordance with Regulation (EU) No 1272/2008:**

Pictograms:



Signal Word:

**Danger**

H statements:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H411	Toxic to aquatic life with long lasting effects.

P statements:

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 2 of 12

Print date: 15/11/2016

P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P370+P378 In case of fire: Use extinguisher powder or CO<sub>2</sub> for extinction.

EUH statements:

EUH066 Repeated exposure may cause skin dryness or cracking.  
Restricted to professional users.

Contains:

tetrachloroethylene

ethyl acetate

N,N-dimethylformamide, dimethyl formamide

### 2.3 Other hazards.

The product may have the following additional risks:  
High potency for odour or taste.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 616-001-00-X CAS No: 68-12-2 EC No: 200-679-5 Registration No: 01-2119475605-32-XXXX	[1] [4] N,N-dimethylformamide, dimethyl formamide	>=25% <50%	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Eye Irrit. 2, H319 - Repr. 1B, H360D ***	-
Index No: 602-028-00-4 CAS No: 127-18-4 EC No: 204-825-9 Registration No: 01-2119475329-28-XXXX	[1] tetrachloroethylene	>=25% <50%	Aquatic Chronic 2, H411 - Carc. 2, H351	-
Index No: 607-022-00-5 CAS No: 141-78-6 EC No: 205-500-4 Registration No: 01-2119475103-46-XXXX	[1] ethyl acetate	>=25% <50%	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

\* \*\*\* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

[4] Substance included in the list established under Article 59, paragraph 1, REACH (Candidate or subject to authorization).

## SECTION 4: FIRST AID MEASURES.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 3 of 12

Print date: 15/11/2016

### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

### Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

### **4.2 Most important symptoms and effects, both acute and delayed.**

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

Toxic Product, accidental contact may result in serious respiratory difficulties, alteration of the central nervous system and in extreme cases, unconsciousness. Immediate medical assistance is required.

### **4.3 Indication of any immediate medical attention and special treatment needed.**

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

## **SECTION 5: FIREFIGHTING MEASURES.**

The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

### **5.1 Extinguishing media.**

#### **Recommended extinguishing methods.**

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

### **5.2 Special hazards arising from the mixture.**

#### **Special risks.**

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

#### **Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### **6.1 Personal precautions, protective equipment and emergency procedures.**

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### **6.2 Environmental precautions.**

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### **6.3 Methods and material for containment and cleaning up.**

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate de-

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 4 of 12

Print date: 15/11/2016

contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## SECTION 7: HANDLING AND STORAGE.

### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

### 7.3 Specific end use(s).

Electric protection motors and transformers.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
N,N-dimethylformamide, dimethyl formamide	68-12-2	European Union [1]	Eight hours	5 (skin)	15 (skin)
			Short term	10 (skin)	30 (skin)
		United Kingdom [2]	Eight hours	5	15
			Short term	10	30
tetrachloroethylene	127-18-4	United Kingdom [2]	Eight hours	50	345
			Short term	100	689
ethyl acetate	141-78-6	United Kingdom [2]	Eight hours	200	
			Short term	400	

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 5 of 12

Print date: 15/11/2016

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
N,N-dimethylformamide, dimethyl formamide N. CAS: 68-12-2 N. CE: 200-679-5	DNEL (Workers)	Inhalation, Long-term, Local effects	15 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Local effects	15 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	15 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	15 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Systemic effects	30 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Systemic effects	30 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	30 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	30 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	3,31 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	1,98 (mg/kg bw/day)
	DNEL (Workers)	Dermal, Acute, Systemic effects	26,3 (mg/kg bw/day)
	DNEL (General population)	Dermal, Acute, Systemic effects	15,8 (mg/kg bw/day)
	DNEL (Workers)	Dermal, Long-term, Local effects	446 (µg/cm <sup>2</sup> )
	DNEL (General population)	Dermal, Long-term, Local effects	267 (µg/cm <sup>2</sup> )
	DNEL (Workers)	Dermal, Acute, Local effects	5900 (µg/cm <sup>2</sup> )
	DNEL (General population)	Dermal, Acute, Local effects	3550 (µg/cm <sup>2</sup> )
	DNEL (General population)	Oral, Long-term, Systemic effects	1,98 (mg/kg bw/day)
	DNEL (General population)	Oral, Acute, Systemic effects	5,94 (mg/kg bw/day)
tetrachloroethylene N. CAS: 127-18-4 N. CE: 204-825-9	DNEL (Workers)	Inhalation, Long-term, Systemic effects	138 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Long-term, Systemic effects	34,5 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Systemic effects	275 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Systemic effects	138 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	39,4 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	23 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	1,3 (mg/kg bw/day)
ethyl acetate N. CAS: 141-78-6 N. CE: 205-500-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	734 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Long-term, Local effects	734 (mg/m <sup>3</sup> )

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 6 of 12

Print date: 15/11/2016

	DNEL (General population)	Inhalation, Long-term, Local effects	367 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Acute, Local effects	1468 (mg/m <sup>3</sup> )
	DNEL (General population)	Inhalation, Acute, Local effects	734 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Long-term, Systemic effects	63 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	37 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
N,N-dimethylformamide, dimethyl formamide N. CAS: 68-12-2 N. CE: 200-679-5	aqua (freshwater)	30 (mg/L)
	aqua (marine water)	3 (mg/L)
	aqua (intermittent releases)	30 (mg/L)
	PNEC STP	123 (mg/L)
	sediment (freshwater)	115,18 (mg/kg sediment dw)
	sediment (marine water)	11,52 (mg/kg sediment dw)
	soil	56,97 (mg/kg soil dw)
tetrachloroethylene N. CAS: 127-18-4 N. CE: 204-825-9	aqua (freshwater)	0,051 (mg/L)
	aqua (marine water)	0,0051 (mg/L)
	aqua (intermittent releases)	0,0364 (mg/L)
	PNEC STP	11,2 (mg/L)
	sediment (freshwater)	0,903 (mg/kg sediment dw)
	sediment (marine water)	0,0903 (mg/kg sediment dw)
	soil	0,01 (mg/kg soil dw)
ethyl acetate N. CAS: 141-78-6 N. CE: 205-500-4	aqua (freshwater)	0,24 (mg/L)
	aqua (marine water)	0,024 (mg/L)
	aqua (intermittent releases)	1,65 (mg/L)
	sediment (freshwater)	1,15 (mg/L)
	sediment (marine water)	0,115 (mg/L)
	Soil	0,148 (mg/kg soil dw)
	PNEC STP	650 (mg/L)
	oral (Hazard for predators)	0,2 (g/kg food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 7 of 12

Print date: 15/11/2016

<b>Concentration:</b>	<b>100 %</b>		
<b>Uses:</b>	<b>Varnishes and electro enamel thinner.</b>		
<b>Breathing protection:</b>			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
<b>Hand protection:</b>			
PPE:	Non-disposable protective gloves against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.		
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
<b>Eye protection:</b>			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
<b>Skin protection:</b>			
PPE:	Chemical protective clothing		
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.		
CEN standards:	EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.		
PPE:	Anti-static safety footwear against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.		
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345		
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.		
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.		

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

### 9.1 Information on basic physical and chemical properties.

Appearance: Transparent liquid with characteristic odour.

Colour: Colourless.

Odour: Characteristic.

Odour threshold: N.A./N.A.

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 8 of 12

Print date: 15/11/2016

pH: N.A./N.A.  
Melting point: N.A./N.A.  
Boiling Point: 86,452°C  
Flash point: 8°C  
Evaporation rate: N.A./N.A.  
Inflammability (solid, gas): N.A./N.A.  
Lower Explosive Limit: N.A./N.A.  
Upper Explosive Limit: N.A./N.A.  
Vapour pressure: 69.275 hPa. at 20°C.  
Vapour density: 3 (air=1).  
Relative density: 0.902 g/cm<sup>3</sup>  
Solubility: N.A./N.A.  
Liposolubility: Soluble.  
Hydrosolubility: Practically soluble.  
Partition coefficient (n-octanol/water): N.A./N.A.  
Auto-ignition temperature: N.A./N.A.  
Decomposition temperature: N.A./N.A.  
Viscosity: 11 seconds ford cup n° 4.  
Explosive properties: 2.2% - 11% (v/v)  
Oxidizing properties: N.A./N.A.  
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

### 9.2 Other information.

Pour point: N.A./N.A.  
Blink: N.A./N.A.  
Kinematic viscosity: N.A./N.A.  
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

### 10.4 Conditions to avoid.

Avoid any improper handling.

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

## SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

### 11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

-Continued on next page.-



# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 9 of 12

Print date: 15/11/2016

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 2.750 mg/kg

b) skin corrosion/irritation;  
Not conclusive data for classification.

c) serious eye damage/irritation;  
Product classified:  
Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;  
Not conclusive data for classification.

e) germ cell mutagenicity;  
Not conclusive data for classification.

f) carcinogenicity;  
Product classified:  
Carcinogen, Category 2: Suspected of causing cancer.

g) reproductive toxicity;  
Product classified:  
Reproductive toxicant, Category 1B: May damage fertility or the unborn child.

h) STOT-single exposure;  
Product classified:  
Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure;  
Not conclusive data for classification.

j) aspiration hazard;  
Not conclusive data for classification.

### SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

#### 12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
ethyl acetate N. CAS: 141-78-6      EC No: 205-500-4	0,73	-	-	Very low

#### 12.4 Mobility in soil.

No information is available about the mobility in soil.  
The product must not be allowed to go into sewers or waterways.  
Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 10 of 12

Print date: 15/11/2016

### SECTION 13: DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

#### 14.1 UN number.

UN No: UN1263

#### 14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT RELATED MATERIAL, 3, PG II, (D/E)

IMDG: UN 1263, PAINT RELATED MATERIAL, 3, PG II (8°C), MARINE POLLUTANT

ICAO: UN 1263, PAINT RELATED MATERIAL, 3, PG II

#### 14.3 Transport hazard class(es).

Class(es): 3

#### 14.4 Packing group.

Packing group: II

#### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

#### 14.6 Special precautions for user.

Labels: 3



Hazard number: 33

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S – Spills): F-E,S-E

Proceed in accordance with point 6.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 11 of 12

Print date: 15/11/2016

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 1218/2009 (SEVESO III): P5b

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
30. Substances which appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 classified as toxic to reproduction category 1A or 1B (Table 3.1) or toxic to reproduction category 1 or 2 (Table 3.2) and listed as follows: - Reproductive toxicant category 1A adverse effects on sexual function and fertility or on development (Table 3.1) or reproductive toxicant category 1 with R60 (May impair fertility) or R61 (May cause harm to the unborn child) (Table 3.2) listed in Appendix 5 - Reproductive toxicant category 1B adverse effects on sexual function and fertility or on development (Table 3.1) or reproductive toxicant category 2 with R60 (May impair fertility) or R61 (May cause harm to the unborn child) (Table 3.2) listed in Appendix 6	1. Shall not be placed on the market, or used, - as substances, - as constituents of other substances, or, - in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: - either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, - the relevant concentration specified in Directive 1999/45/EC where no specific concentration limit is set out in Part 3 of Annex VI to Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows: 'Restricted to professional users'. 2. By way of derogation, paragraph 1 shall not apply to: (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: - motor fuels which are covered by Directive 98/70/EC, - mineral oil products intended for use as fuel in mobile or fixed combustion plants, - fuels sold in closed systems (e.g. liquid gas bottles); (d) artists' paints covered by Directive 1999/45/EC; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date.

### 15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

## SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

## DL101-DISOLVENTE M-2

Version: 2

Revision date: 15/11/2016



Page 12 of 12

Print date: 15/11/2016


H360D May damage the unborn child.  
H411 Toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 [Dermal] : Acute toxicity (Dermal), Category 4  
Acute Tox. 4 [Inhalation] : Acute toxicity (Inhalation), Category 4  
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2  
Carc. 2 : Carcinogen, Category 2  
Eye Irrit. 2 : Eye irritation, Category 2  
Flam. Liq. 2 : Flammable liquid, Category 2  
Repr. 1B : Reproductive toxicant, Category 1B  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Risk classification system NFPA 704:



Health hazard: 3 (Extreme Danger)

Flammability: 4 (Below 73°F)

Reactivity: 0 (Stable)

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
Log Pow: Logarithm of the partition octanol-water.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.