(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915



ROYAL DIAMOND your insulation partner

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: ROYAPOX 915 Product Code: RO113

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Impregnation/ potting / filling resins.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: S.E.G. ROYAL-DIAMOND, S.A.

Address: Polígono Industrial s/n

 City:
 08319 Dosrius

 Province:
 BARCELONA

 Telephone:
 93-791-80-06

 Fax:
 93-791-91-25

E-mail: royaldiamond@royal-insulation.com

Web: www.royal-insulation.com

1.4 Emergency telephone number: 00-34-93-791-80-06 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: Causes serious eye irritation.

Repr. 2: Suspected of damaging fertility or the unborn child.

Skin Irrit. 2: Causes skin irritation.

Skin Sens. 1: May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:







Signal Word:

Warning

H statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child. H411 Toxic to aquatic life with long lasting effects.

P statements:

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915



Version 1 Date of compilation: 21/04/2020 Page 2 of 10 Version 3 (replaces version 2) Revision date: 21/04/2020 Print date: 30/07/2020

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see instructions on this label).

P391 Collect spillage.

P501 Dispose of contents/container according to current local/national legislation.

EUH statements:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains:

reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Boron trichloride amine complex.

2.3 Other hazards.

The product may have the following additional risks: Hazards to soil-dwelling organisms.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit
Index No: 603-074- 00-8 CAS No: 25068-38-6 EC No: 500-033-5 Registration No: 01- 2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)	>=50% <=100%	Aquatic Chronic 2, H411 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 %
CAS No: 34762-90-8	Boron trichloride amine complex.	>2,5% <=10%	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Repr. 2, H361 - Skin Sens. 1B, H317	-
Index No: 603-103- 00-4 CAS No: 68609-97-2 EC No: 271-846-8 Registration No: 01- 2119485289-22-XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	>2,5% <=10%	Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915



Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate

Long-term chronic exposure may result in injury to certain organs or tissues.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

YAL DIAMOND

our insulation partner

(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915



Version 1 Date of compilation: 21/04/2020

Page 4 of 10 Print date: 30/07/2020 **Version 3 (replaces version 2)** Revision date: 21/04/2020

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Chronic 2	200	500

7.3 Specific end use(s).

Electric protection motors and transformers.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
reaction product: bisphenol-A-(epichlorhydrin), epoxy	DNEL	Inhalation, Long-term, Systemic effects	12,25
resin (number average molecular weight ≤ 700)	(Workers)		(mg/m³)
CAS No: 25068-38-6			
EC No: 500-033-5			
avivana mana[(C12, 14 alladava)maathud] daviva	DNEL	Inhalation, Long-term, Local effects	0,98
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. CAS No: 68609-97-2	(Workers)		(mg/m³)
EC No: 271-846-8	DNEL	Inhalation, Long-term, Systemic effects	13,8
EC NO. 2/1-040-0	(Workers)		(mg/m^3)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

(in accordance with Regulation (EU) 2015/830)



RO113-ROYAPOX 915

Version 1 Date of compilation: 21/04/2020

Page 5 of 10 Print date: 30/07/2020 Version 3 (replaces version 2) Revision date: 21/04/2020

Concentration: 100 % Impregnation/ potting / filling resins. **Uses: Breathing protection:** PPF: Filter mask for protection against gases and particles. «CE» marking, category III. The mask must have a wide field of vision and an Characteristics: anatomically designed form in order to be sealed and watertight. CEN standards: EN 136, EN 140, EN 405 Should not be stored in places exposed to high temperatures and damp environments before use. Special Maintenance: attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach Observations: the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer. Filter Type needed: Hand protection: PPE: Protective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or Maintenance: Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Observations: Always use with clean, dry hands. Breakthrough time Material thickness Material: PVC (polyvinyl chloride) > 480 0,35 (min.): (mm): Eye protection: PPE: Face shield. Characteristics: «CE» marking, category II. Face and eye protector against splashing liquid. EN 165, EN 166, EN 167, EN 168 CEN standards: Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should Maintenance: be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly. Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm Observations: vertically once attached to the frame. Skin protection: PPF: Anti-static protective clothing. «CE» marking, category II. Protective clothing should not be too tight or loose in Characteristics: order not to obstruct the user's movements. CEN standards: EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5 In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance: the manufacturer. The protective clothing should offer a level of comfort in line with the level of protection provided in Observations: terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use. PPF: Anti-static safety footwear. Characteristics: «CE» marking, category II. EN ISO 13287, EN ISO 20344, EN ISO 20346 CEN standards: Maintenance: The footwear should be checked regularly The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different Observations: widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Translucent liquid.

Colour: Yellowish. Odour: Characteristic. Odour threshold: N.A./N.A. pH: 8 (conc. 50% water). Melting point: N.A./N.A.

(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915



Boiling Point: 200°C Flash point: 142°C Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A.

Vapour pressure: 0.00001 kPa (0.000075 mm Hg)

Vapour density: N.A./N.A.

Relative density: $1.15 \pm 0.01 \text{ g/cm}^3$

Solubility: N.A./N.A.

Liposolubility: Soluble in most organic solvents. Hydrosolubility: Practically immiscible. Partition coefficient (n-octanol/water): 3.8 Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A. Viscosity: 3000 ± 300 mPa.s

Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases
- Oxidizing agents.

10.6 Hazardous decomposition products.

Depending on conditions of use can be generated the following products:

- COx (carbon oxides).
- Organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION.

Based on the properties of the epoxy components, and keeping in mind the toxicological data on similar preparations, this preparation can sensitise and irritate the skin, eyes, and respiratory tract.

ROYAL DIAMOND

your insulation partner

(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915



The low molecular weight epoxy components are irritants to the eyes, mucous membranes, and skin. Repeated contact with the skin can lead to its irritation or sensitisation, possibly with accentuated autosensitisation to other epoxies.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Product classified:

Reproductive toxicant, Category 2: Suspected of damaging fertility or the unborn child.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

YAL DIAMOND

our insulation partner

(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915



12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA

for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

<u>Sea</u>: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number. UN No: UN3082

14.2 UN proper shipping name.

Description:

ADR: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) / BORON TRICHLORIDE AMINE COMPLEX.), 9, PG III, (-)

IMDG: UN 3082, ENVIRONMÉNTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) / BORON TRICHLORIDE AMINE COMPLEX.), 9, PG III, MARINE POLLUTANT

ICAO/IATA: ÚN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700) / BORON TRICHLORIDE AMINE COMPLEX.), 9, PG III

14.3 Transport hazard class(es).

Class(es): 9

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

ROYAL DIAMOND

your insulation partner

(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915

Version 1 Date of compilation: 21/04/2020

Page 9 of 10 Print date: 30/07/2020 **Version 3 (replaces version 2)** Revision date: 21/04/2020



14.6 Special precautions for user.

Labels: 9



Hazard number: 90 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 30 kg B

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F

Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

This information is shown on the current Safety Data Sheet for the Preparation.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): E2

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Acute 1: Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1: Chronic effect to the aquatic environment, Category 1 Aquatic Chronic 2: Chronic effect to the aquatic environment, Category 2

Eye Irrit. 2: Eye irritation, Category 2 Repr. 2: Reproductive toxicant, Category 2 Skin Irrit. 2: Skin irritant, Category 2 Skin Sens. 1: Skin sensitiser, Category 1 Skin Sens. 1B: Skin sensitiser, Category 1B

(in accordance with Regulation (EU) 2015/830)

RO113-ROYAPOX 915



Version 1 Date of compilation: 21/04/2020 Page 10 of 10 Version 3 (replaces version 2) Revision date: 21/04/2020 Print date: 30/07/2020

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards
Health hazards
Calculation method
Environmental hazards
Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Risk classification system NFPA 704:



Health hazard: 2 (Hazardous)

Flammability: 0 (Will not burn)

Reactivity: 0 (Stable)

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830. Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.