(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

 Version: 3
 Page 1 of 9

 Revision date: 12/01/2017
 Print date: 12/01/2017

# SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: ROYAPOX 959 BLANCA

Product Code: RO122

#### 1.2 Relevant identified uses of the mixture and uses advised against.

Impregnation/ potting / filling resins.

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: S.E.G. ROYAL-DIAMOND, S.A.

Address: Polígono Industrial s/n Citv: 08319 Dosrius

 City:
 08319 Dosrius

 Province:
 BARCELONA

 Telephone:
 93-791-80-06

 Fax:
 93-791-91-25

E-mail: royaldiamond@royaldiamond.es

Web: www.royaldiamond.es

1.4 Emergency telephone number: 00-34-93-791-80-06 (Only available during office hours; Monday-Friday; 08:00-18:00)

#### **SECTION 2: HAZARDS IDENTIFICATION.**

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

#### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

Skin Irrit. 2: Causes skin irritation.

Skin Sens. 1: May cause an allergic skin reaction.

#### 2.2 Label elements.

#### Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:





# Signal Word: **Warning**

H statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

P statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see instructions on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.

(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

 Version: 3
 Page 2 of 9

 Revision date: 12/01/2017
 Print date: 12/01/2017

P391 Collect spillage.

P501 Dispose of contents/container according to current local/national legislation.

EUH statements:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains:

epoxy resin (number average molecular weight ≤ 700),reaction product: bisphenol-A-(epichlorhydrin)

#### 2.3 Other hazards.

The product may have the following additional risks:

Hazards to soil-dwelling organisms.

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.**

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit
Index No: 603-074- 00-8 CAS No: 25068-38-6 EC No: 500-033-5 Registration No: 01- 2119456619-26-XXXX	epoxy resin (number average molecular weight ≤ 700),reaction product: bisphenol-A-(epichlorhydrin)	>=25% <50%	Aquatic Chronic 2, H411 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 %
CAS No: 78-42-2 EC No: 201-116-6	Acido alcohilsulfónico del fenol.	>2,5% <=10%	Skin Irrit. 2, H315	-

<sup>(\*)</sup> The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

#### **SECTION 4: FIRST AID MEASURES.**

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

# 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

#### Eye contact

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

# Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

 Version: 3
 Page 3 of 9

 Revision date: 12/01/2017
 Print date: 12/01/2017

#### Ingestion

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

#### 5.1 Extinguishing media.

# Recommended extinguishing methods.

Extinguisher powder or  $CO_2$ . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

#### 5.2 Special hazards arising from the mixture.

#### Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

#### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

#### 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

# 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

### **SECTION 7: HANDLING AND STORAGE.**

#### 7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers. In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

Version: 3 Revision date: 12/01/2017 Print date: 12/01/2017

**7.2 Conditions for safe storage, including any incompatibilities.**Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Chronic 2	200	500

#### 7.3 Specific end use(s).

Electric protection motors and transformers.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.**

#### 8.1 Control parameters.

The product does NOT contain substances with Professional Exposure Environmental Limit Values. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
epoxy resin (number average molecular weight ≤	DNEL	Inhalation, Long-term, Systemic effects	12,25
700),reaction product: bisphenol-A-(epichlorhydrin)	(Workers)		(mg/m³)
N. CAS: 25068-38-6			
N. CE: 500-033-5			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

#### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.


Concentration:	100 %			
Uses:	Impregnation/ potting / filling resins.			
Breathing protection:				
PPE:	Filter mask for protection against gases and particles.			
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.			
CEN standards:	EN 136, EN 140, EN 405			
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach			
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.			
Filter Type needed:	A2			
Hand protection:				
PPE: Characteristics:	Protective gloves against chemicals. «CE» marking, category III.			
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420			
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.			
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.			

(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

 Version: 3
 Page 5 of 9

 Revision date: 12/01/2017
 Print date: 12/01/2017



#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.**

#### 9.1 Information on basic physical and chemical properties.

Appearance: Viscous liquid.

Colour: White. Odour: Light.

Odour threshold: N.A./N.A. pH: aprox. 7, mixture 1/1 in water

Melting point: N.A./N.A. Boiling Point: 200°C Flash point: 170°C Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: < 0.01 at 20°C. Vapour density: N.A./N.A. Relative density: 1.56 ± 0.04 g/cm<sup>3</sup>

Solubility: N.A./N.A.

Liposolubility: Soluble in the most organic solvents.

Hydrosolubility: Practically insoluble.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A. Viscosity: 11000 ± 2000 mPa.s at 25°C. Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

#### 9.2 Other information.

Pour point: N.A./N.A. Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

Version: 3

Revision date: 12/01/2017 Print date: 12/01/2017

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

#### **SECTION 10: STABILITY AND REACTIVITY.**

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

#### 10.4 Conditions to avoid.

Avoid any improper handling.

#### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

#### **SECTION 11: TOXICOLOGICAL INFORMATION.**

Based on the properties of the epoxy components, and keeping in mind the toxicological data on similar preparations, this preparation can sensitise and irritate the skin, eyes, and respiratory tract.

The low molecular weight epoxy components are irritants to the eyes, mucous membranes, and skin. Repeated contact with the skin can lead to its irritation or sensitisation, possibly with accentuated autosensitisation to other epoxies.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

# 11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

....

 Version: 3
 Page 7 of 9

 Revision date: 12/01/2017
 Print date: 12/01/2017

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Not conclusive data for classification.

i) aspiration hazard;

Not conclusive data for classification.

#### **SECTION 12: ECOLOGICAL INFORMATION.**

#### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

#### 12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

#### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

### **SECTION 13: DISPOSAL CONSIDERATIONS.**

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

#### **SECTION 14: TRANSPORT INFORMATION.**

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**<u>Land</u>**: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

<u>Sea</u>: Transport by ship: IMDG. Transport documentation: Bill of lading

<u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

 Version: 3
 Page 8 of 9

 Revision date: 12/01/2017
 Print date: 12/01/2017

# **14.1 UN number.** UN No: UN3082

#### 14.2 UN proper shipping name.

Description:

ADR: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700), REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN)), 9, PG III, (E) IMDG: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700), REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN)), 9, PG III, MARINE POLLUTANT

ICAO: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq$  700), REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN)), 9, PG III

#### 14.3 Transport hazard class(es).

Class(es): 9

#### 14.4 Packing group.

Packing group: III

#### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

#### 14.6 Special precautions for user.

Labels: 9



Hazard number: 90 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 30 kg B

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F Proceed in accordance with point 6.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

#### **SECTION 15: REGULATORY INFORMATION.**

This information is shown on the current Safety Data Sheet for the Preparation.

#### 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): E2

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

(in accordance with Regulation (EU) 2015/830)

# **RO122-ROYAPOX 959 BLANCA**

 Version: 3
 Page 9 of 9

 Revision date: 12/01/2017
 Print date: 12/01/2017

#### 15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

#### **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

#### Classification codes:

Aquatic Chronic 2: Chronic effect to the aquatic environment, Category 2

Eye Irrit. 2 : Eye irritation, Category 2 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Risk classification system NFPA 704:



Health hazard: 1 (Slightly Hazardous)

Flammability: 0 (Will not burn)

Reactivity: 0 (Stable)

#### Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

# Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/

Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

ROYALIDAMOND